

ECE TYPE-APPROVAL CERTIFICATE



Concerning:2 Approval granted

Approval extended Approval refused Approval withdrawn

Production definitively discontinued

Of a	type of vehicle/component/separate technical unit ² with regard to	Regulation No. 10.	
Appı	roval No: <u>E24*10R06/02*6130*00</u>		
Reason for extension:		-N/A	
1.	Make (trade name of manufacturer):		
2.	Type:	H7	
3.	Means of identification of type, if marked on the vehicle/component/separate technical unit ² :	Approval Mark	
3.1	Location of that marking:	Lable attached to the housing	
4.	Category of vehicle:	N/A	
5.	Name and address of manufacturer:		
6.	In the case of components and separate technical units, location and method of affixing of the approval mark:	More details refer to drawing on page 5 og information document	
7.	Address(es) of assembly plant(s):		



Approval No: <u>E24*10R06/02*6130*00</u>

8. Additional information (where applicable):

9. Technical service responsible for carrying out the tests:

hay Brene

10. Date of test report:

11. Number of test report:

12. Remarks (if any):

13. Place:

14. Date:

15. Signature:

See appendix below

CETOC Technical Service srl Via della Bufalotta, 374, 00139 Roma

20.08.2024

CN-40-17-425-COM24-19005-IR

General commercial description: LED HEADLIGHT BULB Driver

Dublin

10th September, 2024



16. The index to the information package lodged with the approval authority, which may be obtained on Request, is attached.

^{1.} Distinguishing number of the country which issued/extended/refused or withdrawn approval. (see Regulation, provisions on approval).

^{2.} Strike out what does not apply.



Appendix

To type-approval communication concerning the type approval of an electrical/electronic sub-assembly under Regulation No.10.

1.	Additional information	
1.1.	Electrical system rated voltage:	DC 12V, negative ground
1.2.	This ESA can be used on any vehicle type with the following restrictions:	See manufacturer's specifications.
1.2.1	Installation conditions, if any:	See manufacturer's specifications.
1.3.	This ESA can only be used on the following vehicle types:	N/A
1.3.1	Installation conditions, if any:	N/A
1.4.	The specific test method(s) used and the frequency ranges covered to determine immunity were:	Bulk Current Injection Method: Frequency: (20 – 400 MHz) Absorber Chamber Test: Frequency: (400 – 2000 MHz)
1.5.	Laboratory accredited to ISO 17025 and recognized by the Approval Authority responsible for carrying out the tests:	CETOC Technical Service srl
2.	Remarks:	N/A
2.	Remarks: Appendix to type-approval communication concern type approval of a vehicle under Regulation No	ning the
2.	Appendix to type-approval communication concern	ning the
	Appendix to type-approval communication concern type approval of a vehicle under Regulation No	ning the
1.	Appendix to type-approval communication concern type approval of a vehicle under Regulation No Additional information	ning the .10.
1. 2.	Appendix to type-approval communication concern type approval of a vehicle under Regulation No Additional information Electrical system rated voltage:	ning the .10.
1. 2. 3.	Appendix to type-approval communication concern type approval of a vehicle under Regulation No Additional information Electrical system rated voltage: Type of bodywork: List of electronic systems installed in the tested vehicle(s)	ning the .10. N/A N/A
1. 2. 3. 4.	Appendix to type-approval communication concern type approval of a vehicle under Regulation No Additional information Electrical system rated voltage: Type of bodywork: List of electronic systems installed in the tested vehicle(s) not limited to the items in the information document: Vehicle equipped with 24 GHz short-range radar equipment	ning the .10. N/A N/A N/A



Date of issue:

Index to the Information Package

10th September, 2024

	Date of latest amendment:	N/A
	Reason for extension/revision:	N/A
1.	Additional conditions, and advisory notes on legal alternatives.	
2.	Test report(s)	
	- numbers(s):	CN-40-17-425-COM24-19005-IR
	- date of issue:	20.08.2024
	- date of latest amendment:	N/A
3.	Information document	
	- number(s):	H7-00-R10
	- date of issue:	08.08.2024
	- date of latest amendment:	N/A
	Documentation:	23 pages



Appendix: Additional conditions, and advisory notes on legal alternatives

A: Additional conditions:

- 1. The attached technical report, with any of its attachments, forms part of this Type Approval certificate.
- 2. Each device from series production shall be to the measurements specified in the attached drawings, and shall be manufactured only from the materials specified in the Approval documents.
- 3. Changes in the type are permitted only with the explicit permission of NSAI. Breaches of this requirement will lead to a withdrawal of the Type Approval, and in addition may be subject to criminal prosecution.
- 4. At regular intervals, any tests or associated checks prescribed by the applicable legislation to verify continued conformity with the approved type shall be carried out. The manufacturer shall demonstrate compliance with this by submitting to NSAI evidence of adequate arrangements and documented control plans for each type approved.
- 5. Any set of samples or test pieces showing evidence of non-conformity shall give rise to further sampling and testing and all steps shall be taken to restore conformity of production.
- 6. This Type Approval will expire when it is surrendered by the holder, or withdrawn by NSAI, or when the approved type no longer conforms to legal requirements. The recall of the Type Approval can be issued by NSAI when the conditions required for the issuing or continuation of the Type Approval are no longer current, or when the Approval holder is in breach of the duties attached to the Type Approval, or when it is established that the approved type no longer meets the requirements of traffic safety.
- 7. Changes in the company name, address or manufacturing site, as well as in any of the sales or other agents specified in the issuing of the approval must immediately be notified to NSAI.
- 8. The duties imposed by the issuing of this certificate are not transferable. The legal protection of third parties is not affected by this certificate.
- 9. When the manufacture or sale of the system, component or separate technical unit has not been started within one year of the date of issue of this certificate, then NSAI is to be informed. This requirement also applies when the manufacture or sale has been halted for more than one year, or when it ought to have been halted for more than one year. The initial commencement of manufacture or sale, or the resumption of manufacture or sale, shall then be notified to NSAI within one month of commencement or resumption.

B: Legal Options:

Any objection to the requirements set out in this certificate shall be made within one month of the date of issue. The objection shall be made, in writing, to NSAI in Dublin.

Type: H7 Date: **29/08/2024** Ext.:00

GENERAL

1. Make (trade name of manufacturer):

2. Type: H7

Variants: H1, H3, H4, H8, H9, H11, H15, 9005(HB3),9006(HB4), 9012(HIR2), D1S, D2S, D3S, D4S, D5S, D8S

Remark: the above model products, in addition to different models and the lamp socket, the tested sample (H7) are the same to the circuit design, wiring diagrams and components.

General commercial description(s): LED HEADLIGHT BULB Driver

- Means of identification of type, if marked on the component/separate technical unit (a): Approval Mark
- 3.1 Location of that marking: Lable attached to the housing.
- Name and address of manufacturer:

Name and address of authorised representative: N/A

- 5. In the case of components and separate technical units, location and method of affixing of the ECE approval mark: **more details refer to drawing on page 5.**
- 6. Address(es) of assembly plant(s):
- This ESA shall be approved as a component/STU.
- 8. Any restrictions of use and conditions for fitting: N/A
- 9. Electrical system rated voltage: 12 V , Positive/ negative ground
- 10. Charger: N/A
- 11. Charging current: N/A
- 12. Maximal nominal current (in each mode if necessary): N/A
- 13. Nominal charging voltage: N/A
- 14. Basic ESA interface functions: N/A
- 15. Minimum Rsce value (see paragraph 7.11. of this Regulation): N/A